


Residential Energy Storage Battery (Floor-mounted)

LF51.2-300



Compact Size

Minimum the footprint



Eco-Friendly

Clean energy



Long Lifespan

Sustainable long cycles



Built-in BMS

Charge & discharge protection

Product Introduction



Up to 15 units of parallel connections,
flexible capacity expansion



Compatible with mainstream inverters in the
market, providing more options



LCD display for voltage, current, temperature,
convenient for users to query



Built-in BMS provides multiple protection
functions

Residential Energy Storage Battery (Floor-mounted)



Item	Parameters
Battery Model	LF51.2-300
Rated Capacity (5HR)	300 Ah
Nominal Voltage	51.2 V
Rated Energy	15.36 kWh
Discharge Cut-off Voltage	43.2 V
Maximum Charge Voltage	58.4 V
Max. Charge/Discharge Current	100/200 A
Weight	Approx.118 Kg
Function	LCD/WiFi/Bluetooth
Communication Interface	RS485/RS232/CAN
Number of parallel connections	Up to 15 units
Dimensions (W*D*H)	390*256.5*882mm
Design life	More than 15 years
Cycle Life	More than 6000 cycles @ 80% DOD
Ingress Protection	IP31
Case Material	SPCC
Operation Temperature	Charging: 0 to +45°C Discharging: -10 to +55°C Storage: -20 to +60°C
Compatible Inverters	PYLON, Sacolar, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, Victron, SMK, BlueSun

*This list only indicates that our battery is compatible with these inverter brands, which does not imply that they have been officially approved by the inverter manufacturers.