Residential Energy Storage Battery (Floor-mounted)

LF51.2-400

LEOCH BATTERY



Compact Size
Minimum the footprint

Eco-Friendly
Clean energy

Long Lifespan
Sustainable long cycles

Built-in BMS
Charge & discharge protection

Product Introduction

- Up to 15 units of parallel connections, flexible capacity expansion
- Compatible with mainstream inverters in the market, providing more options
- LCD display for voltage, current, temperature, convenient for users to query
- Built-in BMS provides multiple protection functions

Residential Energy Storage Battery (Floor-mounted)

Item	Parameters
Battery Model	**LF51.2-400**
Rated Capacity (5HR)	400 Ah
Nominal Voltage	51.2 V
Rated Energy	20.48 kWh
Discharge Cut-off Voltage	43.2 V
Maximum Charge Voltage	58.4 V
Max. Charge/Discharge Current	200/200 A
Weight	Approx.173 Kg
Function	LCD/WiFi/Bluetooth
Communication Interface	RS485/RS232/CAN
Number of parallel connections	Up to 15 units
Dimensions (W*D*H)	540*280*940mm
Design life	More than 15 years
Cycle Life	More than 6000 cycles @ 80% DOD
Ingress Protection	IP31
Case Material	SPCC
Operation Temperature	Charging: 0 to +45℃ Discharging: -10 to +55℃ Storage: -20 to +60℃
Compatible Inverters	PYLON, Sacolar, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, Victron, SMK, BlueSun

*This list only indicates that our battery is compatible with these inverter brands, which does not imply that they have been officially approved by the inverter manufacturers.

©LEOCH. All rights reserved.
Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice E&OE.

Publication No.:LFELI-51400H-A-EN-V1.0-202512
E-mail: info.lithium@leoch.com
Tel: +86-755-86036060