


Residential Energy Storage Battery (Rack-mounted)



LR51.2-200



Compact Size

Minimum the footprint



Eco-Friendly

Clean energy



Long Lifespan

Sustainable long cycles



Built-in BMS

Charge & discharge protection

Product Introduction



Up to 15 units of parallel connections,
flexible capacity expansion



LCD display for voltage, current, temperature,
convenient for users to query



Compatible with mainstream inverters in the
market, providing more options



Built-in BMS provides multiple protection
functions

Item	Parameters
Battery Model	LR51.2-200
Rated Capacity (5HR)	200Ah
Nominal Voltage	51.2V
Rated Energy	10.24kWh
Discharge Cut-off Voltage	43.2V
Maximum Charge Voltage	57.6V
Max. Charge/Discharge Current	150A
Weight	Approx. 82 Kg
Display	With display screen
Communication Interface	RS485/RS232/CAN
Number of parallel connections	Up to 15 units
Dimensions (W*D*H)	442 *550 *244mm
Design life	More than 15 years
Cycle Life	More than 6000 cycles @ 80% DOD
Ingress Protection	IP31
Case Material	SPCC
Operation Temperature	Charging: 0 to +45℃ Discharging: -10 to +55℃ Storage: -20 to +60℃
Compatible Inverters	PYLON, Sacolar, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, Victron, SMK, BlueSun

*This list only indicates that our battery is compatible with these inverter brands, which does not imply that they have been officially approved by the inverter manufacturers.