Residential Energy Storage Battery (Low Voltage & Stackable)



SOL-5L-B





High Efficiency

Max. efficiency 94%



Easy installation

50 Kg Battery modules



Safe and Reliable

Lithium iron phosphate battery cells



Perfect Compatibility

Work with leading branded inverters

Product Information



Compatible with a variety of mainstream inverter

Maximum Flexibility for any Applications with up to 12 Modules Connected in Parallel



Stackable design,effortlessly installation

Capable of High-Powered Emergency-Backup and Off-Grid Function

[分] Battery Module

- 5.12 kWh per Module
- Modular and Stack Installation Design to simplify the maintenance
- Connect up to 12 module in parallel for a maximum size of 60 kWh

Residential Energy Storage Battery (Low Voltage & Stackable)



Flexible, Efficient, Simple Plug Connection No Additional Wiring Required Tailored Sizing for Each Application Flexible, Efficient, Simple Extend Anytime Easily Adapts to New Requirements Flexible, Efficient, Simple Flexible, Efficient, Simple

| Technical Parameters | | |
|--------------------------------------|--|-------|
| Battery Model | SOL-5L-B | |
| Combination Method | 16S1P | |
| Rated Capacity | Typical | 100Ah |
| | Minimum | 98Ah |
| Nominal Voltage | 51.2V | |
| Discharge Cut-off Voltage | 43.2V | |
| Maximum Charge Voltage | 57.6V | |
| Impedance(single battery pack) | ≤20mΩ | |
| Maximum Continuous Charge Current | 100A | |
| Maximum Continuous Discharge Current | 100A | |
| Operation Temperature Range | Charge:0~50°C/ Discharge: -10~50°C | |
| Storage Temperature Range | -20~+60 °C ,Recommend: ≤60±25%RH storage humidity | |
| Single Battery Pack Dimension/Weight | 680*429*215mm /50Kg±1Kg | |
| System Dimension/Weight | 680*429*320mm /65Kg±1Kg | |
| Compatible Inverters | PYLON, Sacolar, Growatt, Sofar, Voltronic, LUX, Schneider, Afore, Sinexcel, Sorotec, GoodWe, KSTAR, Srne, Must, Megarevo, Sol-Ark, INVT, Aiswei, TBB, SAKO, Solis, Victron, SMK, BlueSun | |