

LEOCH DU230V150(230.4V150Ah)

DU230V150



LEOCH provides safe and efficient LFP battery solutions.

LEOCH DU system uses lithium iron phosphate battery cells, which can be applied in the field of DC screen backup power. It adopts self-developed battery cells and is an emergency backup solution for 60 minutes or more.


Characteristic

- Safe, reliable, and long-life
- Flexible design, modular structure, scalable
- Gapless power supply
- Can communicate with DC screens or monitoring systems, compatible with multiple protocols
- Standard human-machine interface HMI
- Lithium iron phosphate battery cell with high energy conversion efficiency and long service life

System Installation Rendering



PACK Diagram



System Specifications

Nominal Voltage	230.4V
Nominal Capacity	150Ah
Voltage Range	201.6V~248.4V
Cell Specification	3.2V/150Ah
Series/Parallel configuration	12S1P
Energy	34.56KWh
Nominal Power	34.56KW
Max. Output Power	34.56KW
Backup Time	≥60mins
Single cluster configuration	6 Battery PACK
Pack Dimensions (W*D*H)	450*442*176mm
System Dimensions (W*D*H)	800*600*2260mm
Weight	Approx. 440kg
Communication	CAN/RS485/Dry Contact
Cycle life	3500 cycle
Working Humidity	5%~95%R.H.
Thermal Management	Natural Cooling
Opeating Temperature	Discharge at -20 °C~60 °C Charge at 0 °C~55 °C Storage at 5 °C~ 35 °C
Altitude	Over 2500 meters, special instructions required
IP Grade	IP20